

BLANK PAGE



IS 5522:1992

भारतीय मानक

बर्तनों के लिए स्टेनलैंस इस्पात चद्दरें और पित्तयाँ — विशिष्टि (दूसरा पुनरीक्षण)

Indian Standard

STAINLESS STEEL SHEETS AND STRIPS FOR UTENSILS—SPECIFICATION

(Second Revision)

First Reprint OCTOBER 1996

UDC 669·14·018·8-41

© BIS 1992

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard (Second Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Alloy Steels and Special Steels Sectional Committee had been approved by the Metallurgical Engineering Division Council.

This standard was first published in 1969 and revised in 1978. The following major modifications have been incorporated in this revision.

A survey of overseas standards available for stainless steel utensils showed that only stainless steel conforming to AISI 300 grade series (18/8 type) has been prescribed for manufacture of utensils. Metalurgical Engineering Division Council (MTDC) of BIS, in its recent meeting had examined the issue and decided that only stainless steel of 18/8 type be permitted for household utensils. Accordingly only two grades have been covered.

While finalizing revision of this Indian Standard it was decided by the committee that the test data for low nickel manganese, copper grades of stainless steels and the ferritic stainless steels will be examined by the committee as and when available for incorporation in the Indian Standard.

Steel designations presently specified were posing difficulty in implementation of the standards on stainless steels. It has therefore been felt to specify grade designation aligned with AISI system of designation for ease of rememberance and better implementation.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2: 1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

STAINLESS STEEL SHEETS AND STRIPS FOR UTENSILS — SPECIFICATION

(Second Revision)

1 SCOPE

1.1 This standard covers the requirements for stainless steel in the form of sheets and strips for manufacture of utensils.

2 REFERENCES

The following Indian Standards are necessary adjuncts to this standard:

adjuncts to this standard.				
IS No.	Title			
228	Methods for chemical analysis of steels (Issued in various parts)			
1387 : 1967	General requirements for the supply of metallurgical materials (first revision)			
1500: 1983	Method for Brinell hardness test for metallic materials (second revision)			
1501 (Part 1): 1984	Method for Vickers hardness test for metallic materials: Part 1 HV 5 to HV 100 (second revision)			
1586 : 1988	Method for rockwell hard- ness test for metallic material (Scales A-B-C-D-E-F-G-H- K) (second revision)			
1608:1972	Method for tensile testing of steel products (first revision)			
1663:1972	Method for tensile testing of steel sheet and strip of thickness 0.5 mm to 3 mm (first revision)			
1762 (Part 1) : 1974	Code for designation of steels: Part 1 Based on letter symbols (first revision)			
1956 (Part 4): 1975	Glossary of terms relating to iron and steel: Part 4 Steel sheet and strip			
10175: 1982	Modified Erichsen cupping			

3 TERMINOLOGY

3.1 For the purpose of this standard, the definitions given in IS 1956 (Part 4): 1975 shall apply.

strip

test for metallic sheet and

4 SUPPLY OF MATERIAL

4.1 General requirements relating to the supply of material shall conform to IS 1387: 1967.

5 MANUFACTURE

- 5.1 Unless otherwise agreed to in the order, the processes used in making the steel shall be left to the discretion of the manufacturer. However, the steel shall be fully killed. When so desired, the purchaser shall be informed of the steel making process.
- 5.1.1 Sufficient discard shall be made to ensure freedom from pipe and harmful segregations.

6 FREEDOM FROM DEFECTS

6.1 Stainless steel sheets and strips shall be free from harmful defects, such as scale, rust, blisters, laminations, cracked edges and seams.

NOTE — When coil is supplied, the degree or amount of surface defects may be expected to be more than in cut lengths because of the impossibility of rejecting portions of the coils. This should be taken into account by the purchaser in his assessment of coils.

7 CHEMICAL COMPOSITION

7.1 Ladle analysis of the two grades of sheets and strips shall be as given in Table 1. The analysis of steel shall be carried out according to IS 228 and its relevant parts.

7.1.1 Check Analysis

In case of check analysis, the permissible variation for the limits specified in Table 1 shall be as given in Table 2.

8 PHYSICAL TESTS

8.1 Tensile Test

Test samples shall be cut in such a manner that deformation is avoided as far as possible.

8.2 When tested in accordance with IS 1663: 1972 or IS 1608: 1972, the tensile strength, proof stress and percentage elongation shall be as given in Table 3.

Table 1 Chemical Composition

(Clause 7.1)

Grade Designation		Constituents, Percent						
Letter Symbol [see 1S 1762 (Part 1) : 1974]	Numerical Symbol	Carbon Max	Silicon Max	Manganese Max	Nickel	Chromium	Sulphur Max	Phosphorus Max
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
	ISS							
X04Cr19Ni9	304	0.08	1.0	2.0	8.0 to 10.2	17°5 to 20°0	0.030	0.042
X07Cr18Ni9	302	0.15	1.0	2.0	8.0 to 10.0	17.0 to 19.0	0.030	0.045

Table 2 Permissible Variation Between Specified Analysis and Check Analysis

(Clause 7.1.1)

Sì No.	Element	Permissible Deviation*
(1)	(2)	(3)
		Percent
i)	Carbon	士 0.01
ii)	Silicon	± 0.05
iii)	Manganese	± 0.04
iv)	Nickel	± 0·10
v)	Chromium	± 0.50
vi)	Sulphur	+ 0.002
vii)	Phosphorus	+ 0.010

^{*}In one cast the deviation may occur over the upper value or under the lower value of the specified range in Table 1.

8.3 Hardness Test

The hardness of sheets and strips when determined in accordance with IS 1500: 1983 or IS 1501 (Part 1): 1984 or IS 1586: 1988 shall be as given in Table 3.

8.3.1 One test shall be made on each coil, and for every 100 sheets for each size of the same cast.

8.3.2 Any test, other than those specified in 8.1 and 8.3 may be conducted subject to mutual agreement between the purchaser and the manufacturer.

8.4 Erichsen Cupping Test

8.4.1 Subject to agreement between the purchaser and the manufacturer, one cupping test (see IS 10175: 1982) shall be carried out from each lot of five tonnes of material or part thereof from each cast.

8.4.1.1 Where sheets of more than one thickness are rolled from the same cast, one additional cupping test shall be made for each thickness of sheet.

8.4.1.2 Cupping test shall be applicable only for sheets of drawing, deep drawing and extra deep drawing types having thickness from 0.5 mm to 1.6 mm.

8.4.2 Requirements

The minimum Erichsen values shall be as given below:

	Thickness, mm	Average Depth of Cupping, mr	
Over	Up to and Including	oj Cupping, mm	
0.20	0.80	10.0	
0.80	-	12.0	

Table 3 Mechanical Properties in Annealed/Softened Condition

(Clauses 8.2 and 8.3)

Grade Designation		0'2 Percent	Tensile	Percentage	Hardness, Max		
Letter Symbol see IS 1762 (Part 1): 1974]	Numerical Symbol	Proof Stress N/mm ² Min	Strength N/mm² <i>Min</i>	Elongation Min GL = 50 mm	Brinell HB	Rockwell HRB	Vickers Pyramid
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
	ISS						
X04Cr19Ni9	304	205	490	40	187	90	197
X07Cr18Ni9	302	205	490	40	187	90	197

9 DIMENSIONS

9.1 Stainless steel sheets and strips shall be supplied in the following standard dimensions:

Sheets -- Sheets may be supplied in the following standard width: 600, 750 800, 850, 900, 1 000, 1 100 and 1 200 mm.

The strip width and coil weight (sheet and strip) shall be as agreed to between the purchaser and the manufacturer.

- 9.2 The thickness of sheets and strips shall be 1.25, 1.10, 1.00, 0.90, 0.80, 0.70, 0.60, 0.50, 0.45, 0.40, 0.35, 0.30, 0.25 and 0.20 mm.
- 9.3 The length for sheets and strips shall be as agreed to between the purchaser and the manufacturer.

10 TOLERANCES

10.1 The rolling tolerances for stainless steel sheets and strips shall be as follows:

Width Length	$\begin{array}{l} \textit{Tolerance} \\ \pm \ 1.5 \ \text{mm} \\ + \ 10.0 \ \text{mm} \\ -0 \end{array}$
Thickness:	
2·20 to 0·40 mm	\pm 0.04 mm
Over 0.40 up to and including 0.80 mm	± C·10 mm
Over 0.80 up to and including 1.00 mm	\pm 0·12 mm
Over 1.00 up to and including 1.25 mm	± 0.14 mm

NOTE — Measurement of thickness shall be made at least 10 mm away from the edge of the sheet or strip.

10.2 Camber

Permissible values for camber for cold rolled steel sheets/strips shall be as given in Fig. 1.

11 CONDITIONS OF SUPPLY

- 11.1 Unless specified otherwise, the sheets and strips shall be supplied to any of the following conditions:
 - a) Hot rolled, annealed, pickled and flattened;
 - b) Cold rolled, annealed, pickled and flattened:
 - c) Cold rolled, annealed, pickled, flattened and skin passed:
 - d) Rolled, annealed, pickled, surface polished with 100 grit; and
 - e) Rolled, annealed, pickled, surface polished with 120 grit.

12 PACKING

- 12.1 Stainless steel sheets and strips shall be supplied in bundles or in coils as may be agreed to between the purchaser and the manufacturer. The mass of each bundle or coil shall be between 500 kg to 1 000 kg. However, higher weight bundles and coils may be supplied as agreed to between the manufacturer and the purchaser.
- 12.2 Sheets and strips shall be securely packed in paper and tied round with hoop iron with wooden battens underneath to prevent the sheets from damage during transit.

13 MARKING

- 13.1 Every bundle or package of sheets, strips and coils shall be legibly marked with paint showing the name or trade-mark of the manufacturer, mass, thickness, size, grade and the cast number or identification marks, by which the materials may be traced to the cast or casts from which they are made.
- 13.2 The material may also be marked with the Standard Mark. Details available with Bureau of Indian Standards.




Fig. 1 Plan View of Sheet/Strip Showing Edge Camber

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

Amend No.

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publication), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards Monthly Additions'.

This Indian Standard has been developed from Doc: No. MTD 16 (3886)

Date of Issue

Amendments Issued Since Publication

	<u> </u>
BUREAU OF INDIAN STANDARDS	
Headquarters:	
Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002 Telephones: 323 01 31, 323 83 75, 323 94 02	Telegrams: Manaksanstha (Common to all offices)
Regional Offices:	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	323 76 17, 323 38 41
Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola CALCUTTA 700054	{337 84 99, 337 85 61 337 86 26, 337 91 20
Northern: SCO 335-336, Sector 34-A, CHANDIGARH 160022	$\begin{cases} 60\ 38\ 43 \\ 60\ 20\ 25 \end{cases}$
Southern: C.I.T. Campus, IV Cross Road, MADRAS 600113	{235 02 16, 235 04 42 235 15 19, 235 23 15
Western: Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400093	{832 92 95, 832 78 58 832 78 91, 832 78 92
Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. PATNA. THIRUVANANTHAPURAM.	

Text Affected